RECORDER FIELD DATA TI-13238-A

DFS III SYSTEM

CLIENT	PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE
MOU	1186	NPR 4		Alaska	USA	7	9	6.30	8.30	1-27-76	R Weber	1

LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT / CAL.	PLAY BACK	TIME	SIZE	SHOT TOP / BOT.	NO. CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. SEIS OFFSET	SEIS. DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS. 1	2	4	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB) 1-4/24	5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ.	LOW CUT SLOPE	NOTCH IN / OUT	REMARKS
																																					Fire #001 - 016
26	487	~~[illegible]~~	020	1 A	MOA DPB	115	75	60/90	2			E		10'		1/25	1		✓		6sec		AGC	42 42 36 30 24 18 / 18 24 30 36 42 48						90	FAST	512	124	8	36	out	Used for tests - fire #017 test + B
	487		021	2 B	RAW	125	50	60/75	2							1/25								42 42 30 30 30 24 / 24 30 30 36 42 42													
	488		022	3 A		215	50		2							1/19	2							42 42 30 30 30 30 / 30 30 36 36 42 42													
	489		023	4 A		225	50		2							1/21																					
	490		024	5 A		235	50		2							1/25																					
	491		025	6 A		245	50		2							1/29																					Up Hole Dead
	492		026	7 A		255	50		2							1/33																					" " "
	493		027	8 A		325	50		2							1/25	3																				
	494		030	9 A		400	50		2							1/5	4																				
	495		031	10 A		410	50		2							1/9																					
	496		032	11 A		420	50		2							1/13																					
	497		033	12 A		430	50		2							1/17																					# 48 Dead
	498		034	13 A		500	50		2							1/21																					
	499		035	14 A		515	50		2							1/25																					
	500		036	15 A		525	50		2							1/29																					
	501		037	16 A		550	50		2							1/33																					
	502		040	17 A		600	50	60/75	2							1/37																					# 21 Dead

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB

UPPER SET LIMIT 62.5 %

LOWER SET LIMIT 18 %

FORMAT TYPE:

☐ 9 TRACK ☒ 21 TRACK

GALVO LEVEL:

1-24 48/18 DB AUX 15 DB

OTHER:

MISCELLANEOUS INFORMATION:

RECORDER FIELD DATA TI-13238-A

DFS III SYSTEM

CLIENT	PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE
NAVY	1186	NPR-4		ALASKA	USA	7:00	9:00	8:30	8:30	1/28/75	R. WEIR	1 of 2

IDENTIFICATION LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT / CAL.	PLAY BACK	TIME	SIZE	SHOT TOP / BOT.	NO CAPS	CODE	S.P. OFFSET	SPREAD NO. 1 DIR.	CODE	S.P. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	TAPE SAMPLE RATE MS 1	2	4	RECORD LENGTH	PARITY ERRORS	GAIN MODE	INITIAL GAIN (DB) 1-4/24	5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	FILTERS HIGH CUT FREQ.	LOW CUT FREQ.	LOW CUT SLOPE	NOTCH IN/OUT	REMARKS
16	503	62600	050	1A	MON DPB	10:00	50	60/75	2			E		10'		1/5	1		✓		6SEC		AGC	42 / 30	42 / 30	36 / 36	36 / 36	30 / 42	30 / 42	90	FAST	.768	124	8	36	out	"WATER HOLE"
17	504	67260	051	2A	RAW	10:10	50	60/75	2							1/9																					
18	505		052	3A		10:20	50	60/75	2							1/13																					
19	506		053	4A		10:35	50	60/75	2							1/17																					
20	507		054	5A		10:45	50	60/75	2							1/21																					
21	508		055	6A		11:00	50	60/75	2							1/25																					
22	509		056	7A		11:10	50	60/75	2							1/29																					
23	510		057	8A		11:30	50	60/75	2							1/33																					
24	511		060	9A		12:15	50	60/75	2							1/5	2																				
25	512		061	10A		12:25	50	60/75	2							1/9																					
26	513		062	11A		12:35	50	60/75	2							1/13																					
27	514		063	12A		12:50	50	60/75	2							1/17																					
28	515		064	13A		1:00	50	60/75	2							1/21																					
29	516		065	14A		1:35	50	60/75	2							1/25																					
30	517		066	15A		2:10	50	60/75	2							1/29																					IN ON JUGS
31	518		067	16A		2:15	50	60/75	2							1/33																					#23 DEAD
32	519		070	17A		2:30	50	60/75	2							1/37																					
33	520		071	18A		2:40	50	60/75	2							1/41																					
34	521		072	19A		2:50	50	60/75	2							1/45																					
35	522		073	20A		3:30	50	60/75	2							1/5	3																				
36	523		074	21A		3:40	50	60/75	2							1/5																					
37	524		075	22A		4:00	50	60/75	2							1/9																					
38	525	62607 67260	076	23A		4:15	50	60/75	2							1/13																					NEW TAPE
39	526		077	24A		4:40	50	60/75	2							1/17																					
40	527		100	25A		5:45	50	60/75	2							1/21																					
41	528		101	26A		5:45	50	60/75	2							1/25																					#22 DEADY 1,2,3,
42	529		102	27A		6:00	50	60/75	2							1/29																					
43	530		103	28A		6:10	50	60/75	2							1/33																					

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB
UPPER SET LIMIT 62.5 %
LOWER SET LIMIT 18 %
FORMAT TYPE:
☐ 9 TRACK ☑ 21 TRACK
GALVO LEVEL:
1-~~10~~ 18 DB AUX 15 DB
OTHER:

MISCELLANEOUS INFORMATION:

RECORDER FIELD DATA TI-13238-A

DFS III SYSTEM

CLIENT	PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE
NAVY	1186	NPR-4	USA	ALASKA		7:00	9:00	8:00	8:30	1/28/75	R. WEIR	2 of 2

IDENTIFICATION							SHOT					SPREAD						TAPE					GAIN										FILTERS				REMARKS
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT / CAL.	PLAY BACK	TIME	SIZE	TOP / BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS 1	2	4	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB) 1-4/24	5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ.	LOW CUT SLOPE	NOTCH IN / OUT	
26	531	62601	104	29A	RAW	6:25	50	60/75	2			E		10'		1/37	3		✓		6 sec		AGC	42 30	42 30	36 56	36 36	30 42	30 42	90	FAST	.768	124	8	36	out	
	532		105	30A		6:35	50	60/75	2							1/39																					CDP IN WRONG POSITION
	533		106	31A		7:10	50	60/75	2							1/13	4																				SHOOTING PAST CAMP
	534		107	32A		7:20	50	60/75	2							1/17																					#21 + 28 DEAD
	535		110	33A		7:35	50	60/75	2							1/21																					
	536		111	34A		8:00	50	60/75	2							1/25																					

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB
UPPER SET LIMIT 62.5 %
LOWER SET LIMIT 18 %
FORMAT TYPE:
☐ 9 TRACK ☑ 21 TRACK
GALVO LEVEL:
1-~~48~~ 18 DB AUX 15 DB
OTHER:

MISCELLANEOUS INFORMATION:

RECORDER FIELD DATA TI-13238-A

DFS III SYSTEM

CLIENT	PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE
NAVY	1186	NPR-4		ALASKA		7:00	7:30		8:30	1/20/76	R. WEIR	1 of

IDENTIFICATION							SHOT					SPREAD						TAPE				GAIN									FILTERS				
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT / CAL	PLAY BACK	TIME	SIZE	TOP / BOT	NO. CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS 1	2	4	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB) 1-4/24	5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ.	LOW CUT SLOPE	NOTCH IN / OUT
26	537	62601	114	1A	RAW ~~DPB~~	8:50	50	~~60~~/75	2			E		10'		1/17	1		✓		6 SEC	1	AGC	42 30	42 30	36 36	36 36	30 42	30 42	90	FAST	.768	124	8	36	out
	538		115	2A		9:05	50	60/75	2							1/21																				
	539		116	3A		9:15	50	60/75	2							1/25																				
	540		117	4A		9:20	50	60/75	2							1/29																				
	541		120	5A		9:30	50	60/75	2							1/33																				
	542		121	6A		9:50	50	60/75	2							1/37																				
	543		122	7A		10:00	50	60/75	2							1/41																				
	544		123	8A		10:10	50	60/75	2							1/45																				
	545		124	9A		11:40	50	60/75	2							1/1	2															.640				
	546		125	10A		11:50	50	60/75	2							1/5																				
	547		126	11A		12:00	50	60/75	2							1/9																				
	548		127	12A		12:05	50	60/75	2		40'					1/13																				
	549		130	13A		12:20	50	60/75	2		~~500~~ W					1/17																				
	550		131	14A		12:30	50	60/75	2							1/21																				
	551		132	15A		12:40	50	60/75	2							1/25																				
	552		133	16A		12:50	50	60/75	2		165' E					1/29																				
	553		134	17A		1:00	50	60/75	2							1/33																				
	554		135	18A		1:05	50	60/75	2							1/37																				
	555		136	19A	DPB	1:15	50	60/75	2							1/41																				
	556		137	20A	RAW	1:25	50	60/75	2							1/45																				
	557		140	21A		1:30	50	60/75	2							1/49																				
	558		141	22A		2:10	50	60/75	2							1/5	3																			
	559		142	23A		2:35	50	60/75	2							1/9								42 30	42 36	42 42	42 42	36 42	30 42							
	560		143	24A		2:45	50	60/75	2							1/13																				
	561		144	25A		2:55	50	60/75	2							1/17																				
	562		145	26A		3:00	50	60/75	2							1/21																				
	563		146	27A		3:10	50	60/75	2							1/25																				
	564		147	28A		3:20	50	60/75	2							1/29																				

REMARKS: File #112 & 113 used for tests.

Received ITB

Waiting on Drills & Camp

#24 DEAD Dead Up-Hole

ITB

Dead Up-Hole

#48 DEAD

#22 DEAD

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB

UPPER SET LIMIT 62.5 %

LOWER SET LIMIT 18 %

FORMAT TYPE:

☐ 9 TRACK ☑ 21 TRACK

GALVO LEVEL:

1-~~18~~ 18 DB AUX 15 DB

OTHER:

MISCELLANEOUS INFORMATION:

RECORDER FIELD DATA TI-13238-A

DFS III SYSTEM

CLIENT	PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE
NAVY	1186	NPR-4	USA	ALASKA		7:00	7:30	8:00	8:30	1-30-76	R. WEIR	2 of 2

IDENTIFICATION							SHOT					SPREAD						TAPE			GAIN							FILTERS				REMARKS
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT / CAL.	PLAY BACK	TIME	SIZE	TOP / BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS 1	2	4	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB) 1-4/24	5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ.	LOW CUT SLOPE	NOTCH IN / OUT	
26	565	672601 ~~672601~~	150	29A	RAW	3:45	50	60/75	2			E		10'		1/17	4		✓		6 SEC		AGC	42 30	42 36	42 42	42 42	36 42	30 42	90	FAST	~~640~~	124	8	36	out	#22 DEAD?
	566		151	30A		3:55	50	60/75	2							1/21																				DEAD UP HOLE
	567		152	31A		4:15	50	60/75	2		200' S					~~[illegible]~~ 1/1																				*CDP IN WRONG POSITION
	568		153	32A		4:30	50	60/75	2							1/9																				
	569		154	33A		4:40	50	60/75	2							1/13																				
	570	(672602)	155	34A	"	5:25	50	60/75	2							1/17																				#29 DEAD
	571		156	35A		6:05	50	60/75	2		825 W					1/21																				DEAD UP-HOLE
	572		157	36A		6:25	50	60/75	2							1/25																				RECEIVED ITB
	573		160	37A		7:15	50	60/75	2							1/25	5																			~~RECEIVED ITB~~
	574		161	38A		7:25	50	60/75	2							1/29																				
	575		162	39A		7:35	50	~~60/75~~	2		170					1/33																				WATER HOLE
	576		163	40A		7:45	50	60/75	2							1/37																				#38 DEAD

TAPE CHANGE
MEADE RIVER

SHOOTING UNIT BRAKE DOWN

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB
UPPER SET LIMIT 62.5 %
LOWER SET LIMIT 18 %
FORMAT TYPE:
☐ 9 TRACK ☑ 21 TRACK
GALVO LEVEL:
1-~~48~~ 18 DB AUX 15 DB
OTHER:

MISCELLANEOUS INFORMATION:

RECORDER FIELD DATA TI-13238-A

DFS III SYSTEM

CLIENT	PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE
NAVY	1186	NPR 4		Alaska	USA	7:00	8:00		11:00	1-30-76	R Wier	1 of 2

LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT / CAL.	PLAY BACK	TIME	SIZE	SHOT TOP / BOT	NO CAPS	CODE	S.P. OFFSET	SPREAD NO. 1 DIR.	CODE	S.P. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	TAPE SAMPLE RATE MS 1	2	4	RECORD LENGTH	PARITY ERRORS	MODE	GAIN INITIAL GAIN (DB) 1-4/24	5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	FILTERS HIGH CUT FREQ.	LOW CUT FREQ.	LOW CUT SLOPE	NOTCH IN/OUT	REMARKS
																																					FILE 164 to 171 USED FOR TESTS.
26	577	672602	172	1A	MOW DPB	8:35	50	60/75	2			E		10'		1/5	1		✓		6sec		AGC	42 42 42 42 36 30 30 36 42 42 42 42					90	FAST	.640	124	8	36	out	
	578		173	2A	RAW	8:45	50	60/75	2							1/9																					
	579		174	3A		8:55	50	60/75	2							1/13								48 48 48 42 36 30 30 36 42 48 48 48								512					
	580		175	4A		9:30	50	60/75	2							1/17																					FIXING GEOPHONES
	581		176	5A		9:50	50	60/75	2							1/21																					
	582		177	6A	DPB	9:55	50	60/75	2							1/25																640					
	583		200	7A	RAW	10:00	50	60/75	2							1/29								42 42 42 42 36 30 30 36 42 42 42 42													
	584		201	8A		10:10	50	60/75	2							1/33																					#48 DEAD
	585		202	9A		11:20	50	60/75	2							1/5	2																				JUG TRUCK BROKE DOWN
	586		203	10A	DPB	12:15	50	60/75	2							1/9																					MOSTLY LAKE & MARSH
	587		204	11A	RAW	12:25	50	60/75	2							1/13								48 48 48 48 36 30 30 36 48 48 48 48													
	588		205	12A		12:35	50	60/75	2							1/17																					
	589		206	13A		12:45	50	60/75	2							1/21																					
	590	—	207	14A		12:50	50	60/75	2							1/25																					
	591		210	15A		1:45	50	60/75	2							1/5	3																				WAIT ON JUGS
	592		211	16A		2:00	50	60/75	2							1/9																					
	593		212	17A		2:10	50	60/75	2							1/13																					
	594		213	18A		2:20	50	60/75	2							1/17																					
	595		214	19A	DPB	2:30	50	60/75	2							1/21																					RECEIVED ITB.
	596		215	20A		2:40	50	60/75	2							1/25																					
	597		216	21A		2:50	50	60/75	2							1/29																					
	598		217	22A		3:00	50	60/75	2							1/33																					
	599		220	23A		3:30	50	60/75	2							1/5	4																				
	600		221	24A	DPB	3:40	50	60/75	2							1/9																					
	601		222	25A	RAW	3:50	50	60/75	2							1/13																					
	602		223	26A		4:05	50	60/75	2	35'S				20'		1/17																					
	603		224	27A		4:20	50	60/75	2							1/21																					
	604		225	28A		4:30	50	60/75	2							1/25																					ITB

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB
UPPER SET LIMIT 62.5 %
LOWER SET LIMIT 18 %
FORMAT TYPE:
☐ 9 TRACK ☒ 21 TRACK
GALVO LEVEL:
1-~~10~~ 18 DB AUX 15 DB
OTHER:

MISCELLANEOUS INFORMATION:

5X12

RECORDER FIELD DATA TI-13238-A

DFS III SYSTEM

CLIENT	PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE
NAVY	1186	NPR-4		ALASKA	USA	7:00	8:00		11:00	1/31/76	R. WEIR	2 of 2

IDENTIFICATION							SHOT					SPREAD						TAPE					GAIN										FILTERS				REMARKS
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT / CAL.	PLAY BACK	TIME	SIZE	TOP / BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS 1	2	4	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB) 1-4/24	5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ.	LOW CUT SLOPE	NOTCH IN / OUT	
26	605 ~~226~~	672602	226	29A	RAW	4:40	50	60/75	2			E		10'		1/29	4		✓		6 sec		AGC	48 30	48 36	48 48	48 48	36 48	30 48	90	FAST	640	124	8	36	out	ITB
			227													~~1/33~~														CHANGE CLOCK IN RADIO							TEST T.B.
	606		230	30A		5:15	50	60/75	2							1/33														CONTROL UNIT							
	607		231	31A		5:25	50	60/75	2							1/37																					
	608		232	32A		5:35	50	60/75	2		330'E					1/41																					DEAD UP-HOLE
	609		233	33A		6:15	50	60/75	2							1/~~5~~	5																				
	610		234	34A		6:25	50	60/75	2							1/5																					
	611		235	35A		6:35	50	60/75	2							1/9																					#48 DEAD
	612		236	36A		6:45	50	60/75	2							1/13																					#44 "
	613		237	37A		7:00	50	60/75	2							1/17																					#40 "
	614		240	38A		7:15	50	60/75	2							1/21																					36 "
	615		241	39A		7:30	50	60/75	2							1/25																					
	616		242	40A		7:45	50	45/60	2							1/29																					

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT _____ DB
UPPER SET LIMIT _____ %
LOWER SET LIMIT _____ %
FORMAT TYPE:
☐ 9 TRACK ☐ 21 TRACK
GALVO LEVEL:
1-24 _____ DB AUX _____ DB
OTHER:

MISCELLANEOUS INFORMATION:

RECORDER FIELD DATA TI-12238-A

DFS III SYSTEM

CLIENT	PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE
NAVY	1186	NPR-4		ALASKA		7:00	8:00			7/2/76	R. WEIR	1

IDENTIFICATION							SHOT					SPREAD						TAPE				GAIN									FILTERS				REMARKS
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT / CAL	PLAY BACK	TIME	SIZE	TOP / BOT	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS 1	2	4	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB) 1-4/24	5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ	LOW CUT SLOPE	NOTCH IN / OUT	
26-	617	672603	246	1A	now DPB	8:50	50	60/75	2			F		10'		1/5	1		✓		65sec		AGC	42 30	42 36	42 42	42 42	36 42	30 42	90	FBT .640	124	8	36	out	FILE #243 to 245 USED FOR TESTS.
	-618		247	2A	RAW	9:00	50	60/75	2							1/9																				
	-619		250	3A		9:10	50	60/75	2							1/13																				
	620		251	4A		9:20	50	60/75	2							1/17																				
	621		252	5A		9:20	50	60/75	2							1/21																				Noisy Group Caused By Camp
	622		253	6A		9:40	50	60/75	2							1/25																				#47 DEAD
	623		254	7A		9:50	50	60/75	2							1/29																				#43 DEAD
	624		255	8A		10:00	50	60/75	2							1/33																				
	625		256	9A		11:15	50	60/75	2							1/5	2																			
	626		257	10A		11:25	50	60/75	2							1/9																				
	627		260	11A		11:50	50	60/75	2							1/5	3																			
	628		261	12A		12:00	50	60/75	2							1/9																				
	629		262	13A		12:10	50	60/75	2							1/13																				
	630		263	14A		12:15	50	60/75	2							1/17																				
	631		264	15A		12:25	50	60/75	2							1/21								48 30	48 36	48 48	48 48	36 48	30 48							
	632		265	16A		12:35	50	60/75	2							1/25																				
	633		266	17A		1:30	50	60/75	2							1/5	4																			
	634		267	18A		1:40	50	60/75	2							1/9																				
	635		270	19A		1:45	50	60/75	2							1/13																				
	636		271	20A		1:55	50	60/75	2							1/17																				
	637		272	21A		2:05	50	60/75	2							1/21																				
	638		273	22A		2:15	50	60/75	2							1/25																				#38 DEAD AMPLIFIER
	639		274	23A		2:20	50	60/75	2							1/29																				
	640		275	24A		2:30	50	60/75	2							1/33																				
	641		276	25A		3:00	50	60/75	2							1/5	5																			
	642		277	26A		3:10	50	60/75	2							1/9																				
	643		300	27A		3:20	50	60/75	2							1/13																				
	644		301	28A		3:30	50	60/75	2							1/17																				

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB
UPPER SET LIMIT 62.5 %
LOWER SET LIMIT 18 %
FORMAT TYPE:
☐ 9 TRACK ☑ 21 TRACK
GALVO LEVEL:
148/18 DB AUX 15 DB
OTHER:

MISCELLANEOUS INFORMATION:

RECORDER FIELD DATA TI-1323B-A

DFS III SYSTEM

CLIENT	PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE
NAVY	1186	NPR-4		ALASKA	USA	7:00	8:00			2/1/76	R. WEIR	2 of 2

IDENTIFICATION							SHOT					SPREAD						TAPE					GAIN									FILTERS				REMARKS
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT / CAL.	PLAY BACK	TIME	SIZE	TOP / BOT	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS 1	2	4	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB) 1-4/24	5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ	LOW CUT SLOPE	NOTCH IN / OUT	
26	645	672603	302	29A	DBB	3:40	50	60/75	2			E		10'		1/21	6		✓		6 sec		AGC	48 30	48 36	48 48	48 48	36 48	30 48	90	FAST	.640	124	8	36	out	
	646		303	30A	RAW	3:50	50	60/75	2							1/25																				
	647		304	31A		4:00	50	60/75	2							1/29																				
	648		305	32A		4:15	50	60/75	2							1/33																				
	649		306	33A		5:35	50	60/75	2							1/5	7																HOLE BLEW			CDP IN WRONG
	650		307	34A		5:50	50	60/75	2							1/13																				HOLE BLEW
	651		310	35A		6:00	50	60/75	2							1/17																				~~HOLE BLEW~~
	652		311	36A	DBB	6:15	50	60/75	2							1/21																				
	653		312	37A	RAW	6:25	50	60/75	2							1/25																				
	654		313	38A		6:35	50	60/75	2							1/29																				
	655		314	39A		6:45	50	60/75	2							1/33																				
	656		315	40A		7:00	50	60/75	2							1/37																				

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB
UPPER SET LIMIT 62.5 %
LOWER SET LIMIT 18 %
FORMAT TYPE:
☐ 9 TRACK ☑ 21 TRACK
GALVO LEVEL:
1-~~20~~ 18 DB AUX 15 DB
OTHER:

MISCELLANEOUS INFORMATION:

REGORDER FIELD DATA TI-13238-A

DFS III SYSTEM

CLIENT	PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE
NAVY	N86	NPR-4		ALASKA	USA	7:00	7:30	7:30	8:30	2/2/76	R. WEIR	1 of

LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT / CAL.	PLAY BACK	TIME	SIZE	SHOT TOP / BOT.	NO. CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS 1	2	4	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB) 1-4/24	5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ.	LOW CUT SLOPE	NOTCH IN/OUT	REMARKS
																								48	48	48	48	36	36								FILE #316 to 323
26	658	672603	324	1A	MON DAR	8:35	50	60/75	2			E		10'		1/1	1		✓		6sec		AGC	30	36	48	48	48	48	90	FAST	.640	124	8	36	out	USED FOR TESTS.
	658		325	2A	RAW	8:45	50	60/75	2							1/5																					REPLANTED #46
	659		326	3A		8:55	50	60/75	2							1/9																					
	660		327	4A		9:05	50	60/75	2							1/13																					
	661		330	5A		9:15	50	60/75	2							1/17																					
	662		331	6A		9:25	50	60/75	2							1/21																					SHORT RECORD (END OF TAP
	663	672604	332	7A		9:35	50	60/75	2							1/25																					TAPE CHANGE
	664		333	8A		9:45	50	60/75	2							1/29																					
	665		334	9A		11:15	50	60/75	2							1/5	2																				WAITING ON JUGS
	666		335	10A		11:25	50	60/75	2							1/9																					
	667		336	11A		11:30	50	60/75	2							1/13																					
	668		337	12A		11:40	50	60/75	2							1/17																					
	669		340	13A		12:00	50	60/75	2							1/9	3																				REPLANTED SOME JUGS.
	670		341	14A		12:15	50	60/75	2							1/13																					
	671		342	15A		12:25	50	60/75	2							1/17																					
	672		343	16A		12:40	50	60/75	2							1/21																					{ ONE SECOND RECORD
	673		344	17A		1:05	50	60/75	2							1/5	4																				COCKPIT TROUBLE
	674		345	18A		1:15	50	60/75	2							1/9																					
	675		346	19A		1:20	50	60/75	2							1/13																					
	676		347	20A		1:30	50	60/75	2							1/17																					
	677		350	21A		1:50	50	60/75	2							1/19	5																				
	678		351	22A		2:00	50	60/75	2							1/13																					
	679		352	23A		2:10	50	60/75	2							1/17																					TRACE #35 LAYED ON BAR
	680		353	24A		2:20	50	60/75	2							1/21																					ICE - WIND NOISE
	681		354	25A		2:55	50	60/75	2							1/5	6																				TRACE #37 "
	682		355	26A		3:05	50	60/75	2							1/9																					TRACE #38 "
	683		356	27A		3:15	50	60/75	1							1/13																					TRACE #39 "
	684		357	28A		3:25	50	60/75	"							1/17																					" 25 "

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB
UPPER SET LIMIT 62.5 %
LOWER SET LIMIT 18 %
FORMAT TYPE:
☐ 9 TRACK ☒ 21 TRACK
GALVO LEVEL:
1-~~10~~ 18 DB AUX 15 DB
OTHER:

MISCELLANEOUS INFORMATION:

15 10 7

RECORDER FIELD DATA TI-15230-A

DFS III SYSTEM

CLIENT	PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE
NAVY	1186	NPR-4		ALASKA		7:00	7:30	7:30	8:30	2/2/76	R. WEIR	2 of 2

IDENTIFICATION: LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT / CAL.	PLAY BACK	TIME	SHOT: SIZE	TOP / BOT.	NO CAPS	CODE	S.P. OFFSET	SPREAD: NO. 1 DIR.	CODE	S.P. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	TAPE: SAMPLE RATE MS 1	2	4	RECORD LENGTH	PARITY ERRORS	MODE	GAIN: INITIAL GAIN (DB) 1-4/24	5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	FILTERS: HIGH CUT FREQ.	LOW CUT FREQ.	LOW CUT SLOPE	NOTCH IN/OUT	REMARKS
26	685	672604	360	29A	RAW	3:35	50	60/75	2			E		10'		1/21	6		✓		6500		AGC	48 30	48 36	48 48	48 48	36 48	30 48	90	FAST	.640	124	8	36	out	
	686		361	30A		3:45	50	60/75	2							1/25																					
	687		362	31A		3:55	50	60/75	2							1/29																					
	688		363	32A		4:05	50	60/75	2							1/33																					
	689		364	33A		4:00	50	60/75	2							1/5	7																				WAITING ON TUGS
	690		365	34A	DPB	5:15	50	60/75	2							1/9																					
	691		366	35A	RAW	5:25	50	60/75	2							1/13																					
	692		367	36A		5:35	50	60/75	2							1/17																					
	693		370	37A		5:50	50	60/75	2							1/21																					
	694		371	38A		6:00	50	60/75	2							1/25																					
	695		372	39A		6:15	50	60/75	2							1/29																					
	696		373	40A		6:25	50	60/75	2							1/33																					

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB

UPPER SET LIMIT 625 %

LOWER SET LIMIT 18 %

FORMAT TYPE:

☐ 9 TRACK ☑ 21 TRACK

GALVO LEVEL:

1-~~16~~ 18 DB AUX 15 DB

OTHER:

MISCELLANEOUS INFORMATION:

96-1

RECORDER FIELD DATA TI-13238-A

DFS III SYSTEM

CLIENT	PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE
NAVY	1186	NPR 4		ALASKA	USA	7	8			2-4-76	R WEIR	1 of 2

IDENTIFICATION LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT / CAL.	PLAY BACK	TIME	SHOT SIZE	TOP / BOT.	NO CAPS	CODE	S.P. OFFSET	SPREAD NO. 1 DIR.	CODE	S.P. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	TAPE SAMPLE RATE MS 1	2	4	RECORD LENGTH	PARITY ERRORS	GAIN MODE	INITIAL GAIN (DB) 1-4/24	5-8	9-12	13-18	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	FILTERS HIGH CUT FREQ.	LOW CUT FREQ.	LOW CUT SLOPE	NOTCH IN/OUT	REMARKS: tests record # 374 — 376.
26	697	672604	377	1 A	Mon	9:15	50	60/75	2			F		[redacted]		1/5	1		✓		6		A6C	48 / 36	48 / 36	48 / 48	[redacted] / 48	36 / 48	30 / 48	90	Fast	.640	124	[redacted]	36	out	waiting on shooter
	698		400	2 A		9:25	50	60/75	2					[redacted]		1/9																					
	699		401	3 A		9:35	50	60/75	2					10'		1/13																					
	700		402	4 A		9:40	50	60/75	2							1/17																					
	70[redacted]		403	5 A		9:50	50	60/75	2							1/21																					
	[redacted]		404	6 A		10:00	50	60/75	2							1/25																					
	[redacted]		405	7 A		10:05	50	60/75	2							1/29																					
	[redacted]		406	8 A		10:10	50	60/75	2							1/33																					
	70[redacted]		407	9 A		11:55	50	60/75	2							1/5	2																				waiting on Juggs
	706		410	10 A		12:05	50	60/75	2							1/9																					
	707		411	11 A		12:15	50	60/75	2							1/13																					
	708		412	12 A		1230	50	60/75	2							1/17																					
	709		413	13 A	RAW	1:00	50	60/75	2							1/21																					Waiting on Jugs
	710		414	14 A		1:10	50	60/75	2							1/25																					
	711		415	15 A		1:20	50	60/75	2							1/29																					Tape Change
	712	672605	416	16 A		1:35	50	60/75	2							1/29																					CDP Wrong
	713		417	17 A		1:50	60	60/75	2							1/5	3																				Ins
	714		420	18 A		1:55	50	60/75	2							1/9																					"
	715		421	19 A		2:05	50	60/75	2							1/13																					"
	716		422	20 A		2:10	50	60/75	2							1/17																					"
	717		423	21 A		2:15	50	60/75	2							1/21																					"
	718		424	22 A		2:25	50	60/75	2							1/25																					"
	719		425	23 A		2:35	50	60/75	2							1/29																					
	720		426	24 A		2:45	50	60/75	2							1/33																					
	721		427	25 A		3:25	50	60/75	2							1/5	4																				
	722		430	26 A		3:35	50	60/75	2							1/9																					
	723		431	27 A		3:40	50	60/75	2							1/13																					
	724		432	28 A		3:45	50	60/75	2							1/17																					

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB

UPPER SET LIMIT 62.5 %

LOWER SET LIMIT 10 %

FORMAT TYPE:

☐ 9 TRACK ☑ 21 TRACK

GALVO LEVEL:

1 ~~48~~ 18 DB AUX 15 DB

OTHER:

MISCELLANEOUS INFORMATION:

RECORDER FIELD DATA TI-13236-A

DFS III SYSTEM

CLIENT	PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE
NAVY	1186	NPR 4		~~AK~~ ALASKA	USA	7	8			2 4 76	R. WEIR	2 of 2

IDENTIFICATION						SHOT					SPREAD						TAPE					GAIN									FILTERS				REMARKS
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT / CAL.	PLAY BACK	TIME	SIZE	TOP / BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS 1	2	4	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB) 1-4/24	5-9	9-12	13-16	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ	LOW CUT SLOPE	NOTCH IN / OUT	
26	725	672605	433	29 A		4:05	50	60/75	2			E			10'	1/13	4		✓		6		AGC	48/30	48/36	48/48	48/48	36/48	30/40	90	FAST	.640	124	8	36	out	
	726		434	30 A		4:15	50	60/75	2							1/17																					
	727		435	31 A		4:30	50	60/75	2							1/21																					
	728		436	32 A		~~4:35~~	50	60/75	2							1/25																					
	729		437	33 A		5:25	50	60/75	2							1/~~4~~	5																				
	730		440	34 A		5:35	50	60/75	2							1/13																					
	731		441	35 A		5:45	50	60/75	2							1/17																					
	732		442	36 A		6:00	50	60/75	2							1/21																					
	733		443	37 A		6:10	50	60/75	2							1/25																					
	734		444	38 A		6:20	50	60/75	2							1/29																		U/L		DEAD UP-HOLE	
	735		445	39 A		6:30	50	60/75	2							1/33																		L/H		DEAD DN-HOLE	
	736		446	40 A		~~6:40~~	50	60/75	2							1/5	6																			WAITING ON JUGS	
	737		447	41 A		7:40	50	60/75	2							1/9																					
	738		450	42 A		7:50	50	60/75	2							1/13																					
	739		451	43 A		8:00	50	60/75	2							1/17																					
	740		452	44 A		8:10	50	60/75	2							1/21																					
	741		453	45 A		8:20	50	60/75	2							1/25																					
	742		454	46 A		8:30	50	60/75	2							1/29																					
	743		455	47 A		8:40	50	60/75	2							1/33																					
	744		456	48 A		8:50	50	60/75	2							1/37																					

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT _____ DB

UPPER SET LIMIT _____ %

LOWER SET LIMIT _____ %

FORMAT TYPE:

☐ 9 TRACK ☐ 21 TRACK

GALVO LEVEL:

1-24 _____ DB AUX _____ DB

OTHER:

MISCELLANEOUS INFORMATION:

RECORDER FIELD DATA TI-13236-A

DFS III SYSTEM

CLIENT	PARTY NO	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE
NAVY	1186	NPR4		ALASKA	USA	7	8	7:00	9:00	2-5-76	Sherwood & McBeat	1 of

IDENTIFICATION LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT / CAL.	PLAY BACK	TIME	SHOT SIZE	TOP / BOT.	NO CAPS	CODE	S.P. OFFSET	SPREAD NO. 1 DIR.	CODE	S.P. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	TAPE SAMPLE RATE MS 1	2	4	RECORD LENGTH	PARITY ERRORS	GAIN MODE	INITIAL GAIN (DB) 1-4/24	5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	FILTERS HIGH CUT FREQ.	LOW CUT FREQ.	LOW CUT SLOPE	NOTCH IN/OUT	REMARKS
																																					Tests Record # 457
																																					# 466. Inst. Noise test
																																					# 467
26	745	672606	470	1 A		9:15	50	60/75	2			E		10'		1/5	1		V		6		AGC	48/50	45/36	48/48	48/48	36/48	30/48	90	FAST	6/40	124	8	36	out	
	746		471	2 A		9:25	50	60/75	2							1/9																					
	747		472	3 A		9:35	50	60/75	2							1/13																					
	748		473	4 A		9:45	50	60/75	2							1/17																					
	749		474	5 A		9:55	50	60/75	2							1/21																					
	750		475	6 A		10:10	50	60/75	2							1/25																					
	751		476	7 A		10:15	50	60/75	2							1/29																					
	752		477	8 A		11:15	50	60/75	2							1/5	2																				
	753		500	9 A		11:20	50	60/75	2							1/9																					wind 10 mph
	754		501	10 A	DPB	11:35	50	60/75	2							1/13																					
	755		502	11 A		11:45	50	60/75	2							1/17																					cats working off line
	756		503	12 A		12:15	50	60/75	2							1/21										48/48	36/42	30/42									Ploughing step (Gain 36-48)
	757		504	13 A		12:50	50	60/75	2							1/1	3																				ITB
	758		505	14 A		1:25	50	60/75	2							1/5																					test + no brake #505 record # ITB
		602606	507		TEST		Time		BRAKE																											2	on tape record #s 507 & 510
			510			"	"		"																											3	
	759		511	15 A		1:30	50	60/75	2							1/9																					
	760		512	16 A		1:40	50	60/75	2							1/13																					
	761		513	17 A		1:50	50	60/75	2							1/17																					
	762		514	18 A		2:00	50	60/75	2							1/21																					
	763		515	19 A		2:10	50	60/75	2							1/25																					
	764		516	20 A	DPB	2:20	50	60/75	2							1/29																					
	765		517	21 A		2:30	50	60/75	2							1/33																					
	766		520	22 A		2:40	50	60/75	2							1/37																					
	767		521	23 A		2:45	50	60/75	2							1/41										48/48	36/48	30/48									
	768		522	24 A		2:55	50	60/75	2							1/[redacted]																					CDP wrong setting
	769		523	25 A		[redacted] 3:35	50	60/75	2							1/1	4																				
	770		524	26 A		3:45	50	60/75	2							1/9																					

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT _____ DB

UPPER SET LIMIT _____ %

LOWER SET LIMIT _____ %

FORMAT TYPE:

☐ 9 TRACK ☐ 21 TRACK

GALVO LEVEL:

1-24 _____ DB AUX _____ DB

OTHER:

MISCELLANEOUS INFORMATION:

RECORDER FIELD DATA TI-13238-A

DFS III SYSTEM

CLIENT	PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE
NAUY	1186	NPR 4		Alaska	USA	7	8			25-76	Sherwood & Jacobsen	2 of 2

IDENTIFICATION							SHOT					SPREAD						TAPE				GAIN									FILTERS				REMARKS
LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT / CAL.	PLAY BACK	TIME	SIZE	TOP / BOT.	NO. CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. SEIS OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS 1	2	4	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB) 1-4/24	5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ.	LOW CUT SLOPE	NOTCH IN / OUT	
26	771	62606	525	27A		4:00	50	60/75	2			E		10'		1/13	4	✓			6		ACC	48 30	48 36	48 48	48 48	36 48	30 48	90	FAST	640	124	8	36	out	
	772		526	28A		4:10	50	60/75	2							1/17																					
	773		527	29A		4:20	50	60/75	2							1/21																					
	774		530	30A		4:35	50	60/75	2							1/25																					
	775		531	31A		4:50	50	60/75	2							1/29																					
	776		532	32A		5:00	50	60/75	2							1/33																					
	777		533	33A		6:00	50	60/75	2							1/6	5																				
	778		534	34A		6:10	50	60/75	2							1/13																					
	779		535	35A		6:20	50	60/75	2							1/17																					OFFSET 75' N N.UPHOLE
	780		536	36A		6:35	50	60/75	2							1/2																					
	781		537	37A		6:45	50	60/75	2							1/25																					
	782		540	38A		6:50	50	60/75	2							1/29																					
	783		541	39A		7:00	50	60/75	2							1/33																					
	784		542	40A		7:10	50	60/75	2							1/37																					

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT _____ DB

UPPER SET LIMIT _____ %

LOWER SET LIMIT _____ %

FORMAT TYPE:

☐ 9 TRACK ☐ 21 TRACK

GALVO LEVEL:

1-24 _____ DB AUX _____ DB

OTHER:

MISCELLANEOUS INFORMATION:

RECORDER FIELD DATA TI-13238-A

DFS III SYSTEM

CLIENT	PARTY NO.	PROSPECT	COUNTY	STATE	COUNTRY	LEFT STORAGE	ARRIVED FIELD	LEFT FIELD	ARRIVED STORAGE	DATE	OBSERVER	PAGE
NAVY	1196	NPR-4	NORTH SLOPE	ALASKA	U.S.A	7:00AM	8:30	8:00	9:00	2/6/76	R. SHERWOOD - J.D. L. TOLBERT	1

LINE	PROFILE	REEL NUMBER	FILE NUMBER	SHOT / CAL.	PLAY BACK	TIME	SIZE	SHOT TOP / BOT.	NO CAPS	CODE	S.P. OFFSET	NO. 1 DIR.	CODE	S.P. SET OFFSET	SEIS DEPTH	CDP SWITCH	SETUP	SAMPLE RATE MS 1	2	4	RECORD LENGTH	PARITY ERRORS	MODE	INITIAL GAIN (DB) 1-4/24	5-8	9-12	13-16	17-20	21-24	FINAL GAIN DB	RELEASE RATE	TRIP DELAY	HIGH CUT FREQ.	LOW CUT FREQ.	LOW CUT SLOPE	NOTCH IN/OUT	REMARKS DAILY TEST FILES 555-543 45° BELOW ZERO
26	785	672000	556	1 A	DPB	9:30 AM	50	60/75	2			E		10'		1/9	784		✓		6 sec		AGC	48/30	48/36	48/48	48/48	36/48	30/48	90	FAST	640	124	8	36	OUT	SP# 786-791 SKIPED
	792		557	2 A		12:50	50	60/75	2							1/1	798																				WAITING ON CHAINING
	793		560	3 A		1:10	50	60/75	2							1/5																					CREW + Rigs
	794		561	4 A		1:20	50	60/75	2							1/9																					
	795		562	5 A		1:30	50	60/75	2							1/13																					
	796		563	6 A		1:40	50	60/75	2							1/17																					
	797		564	7 A		1:45	50	60/75	2							1/21																					
	798		565	8 A		1:50	50	60/75	2							1/25																					
	799		566	9 A		2:05	50	60/75	2							1/29																					
	800		567	10 A		2:15	50	60/75	2							1/33																					
	801		570	11 A		3:00	50	60/75	2							1/5	806																				
	802		571	12 A		3:20	50	60/75	2							1/9	807																				move up to Replant pegs.
	803		572	13 A		3:30	50	60/75	2							1/9																					
	804		573	14 A		3:35	50	60/75	2							1/13																					
	805		574	15 A		3:45	50	60/75	2							1/17																					
	806		575	16 A		3:55	50	60/75	2							1/21																					
	807		576	17 A		4:10	50	60/75	2							1/25																					
	808		577	18 A		4:15	50	60/75	2							1/29																					
	809		600	19 A		4:55	50	60/75	2							1/33	812																				cable layout slow down
	810		601	20 A		5:30	50	60/75	2							1/17																					to the extreme Cold.
	811		602	21 A		5:35	50	60/75	2							1/21																					50 below +
	812		603	22 A		5:50	50	60/75	2							1/25																					
	813		604	23 A		6:10	50	60/75	2							1/29																					
	814		605	24 A	DPB	6:25	50	60/75	2							1/33																					
	815		606	25 A		6:40	50	60/75	2							1/37																					
	816		607	26 A		6:50	50	60/75	2							1/41																					
	817		610	27 A		7:00	50	60/75	2							1/45																					Shoot 1 CABLE TO COMPLETE TAIL SPREAD 48-45 Dead

SEISMOMETER AND SPREAD INFORMATION

CODE	SEIS. TYPE	NO./GP.	INT.	GROUP PATTERN	GP. INT.	SPREAD PATTERN

SHOT CONFIGURATION

DFS III SYSTEM PARAMETERS:

GAIN CONSTANT 30 DB

UPPER SET LIMIT 62.5 %

LOWER SET LIMIT 18 %

FORMAT TYPE:

☐ 9 TRACK ☑ 21 TRACK

GALVO LEVEL:

1-24 18 DB AUX 15 DB

OTHER:

MISCELLANEOUS INFORMATION: