LAND SEISMIC RECORDING LOG

CLIENT: HUSKY | PROSPECT: NPR-4 | AREA: KEY CREEK | LINE NO: KD-90

PARTY NO: 1182 | INST. ENG: C. BLALOCK, J. WINDHAM | 7-6 | 11 HRS | DATE: MO 4 DAY 26 YR 77

INSTRUMENT (9-TRACK): [X] 1 SYSTEM [ ] 2 SYSTEMS; [X] 1-24 & 25-48 [ ] 1-48 & 49-96; [ ] ODDS & EVENS; TYPE: [ ] DFS III [X] DFS IX [ ] DFS X [ ] OTHER; [ ] 9 TRACK [X] 21 TRACK; FORMAT: SEG TIAC; [ ] GAPPED [ ] UNGAPPED; PACKING DENSITY: (LO) [X] 556 BPI [ ] 800 BPI (HI) [ ] 712 BPI [ ] 1600 BPI

NO. BYTES IN HEADER REC: | NO. BYTES IN RECORD ID: | NO. BYTES PER SCAN: | RECORD NUMBERS: [ ] DEC. [X] OCT | GAIN CONSTANT: 36 db | INPUT IMPEDANCE: 500 ohms.

CONFIGURATION (MAG TAPE): FIELD TRACE NOS.: 1-48 | DATA CHANNEL NOS.: 1-48 (ON MAG TAPE) | AUXILIARY DATA: (1) SPS (2) (3) (4) (5) (6) (7) | AUXILIARY CHANNEL NOS.: 3

PARAMETER: RECORD LENGTH: 6 sec. | SAMPLE RATE: [ ] 1 ms. [ ] 4 ms. [X] 2 ms. [ ] ___ ms. | GAIN MODE: [X] IFP [ ] INITIAL [ ] FINAL [ ] MANUAL [ ] OPERATE | FILTERS: FREQ. 8 LO CUT HZ SLOPE 36 | FREQ. 124 HI CUT HZ SLOPE 72 | NOTCH FILTER: [ ] IN [X] OUT

DISPLAY: MODE: [X] AGC [ ] FLOAT [ ] DEFLOAT [ ] AMPLIFIER [ ] DIRECT | INITIAL GAIN: 18 db | TRIP SENS: 18 db | POLARITY CONVENTION: | PRESSURE INCREASE ON GEOPHONE: [ ] NEGATIVE [ ] POSITIVE } NUMBERS ON MAG. TAPE; [X] DOWNBREAK [ ] UPBREAK } ON DISPLAY

CFS I: TYPE STACK: | GATE LENGTH: | RECORD REJECTION: | NOISE REDUCTION: | NOISE THRESHOLD: | CORR. SCALING: | R.C.U. NORM/ALT SW.

SOURCE: TYPE: [X] DYNAMITE [ ] VIBROSEIS [ ] OTHER | PATTERN: SINGLE HOLE | NO. OF POSITIONS: | INLINE SPACING: | LATERAL SPACING: | STAGGER: | LENGTH: | WIDTH: | LATERAL OFFSET:
CHG/HOLE: 50 | HOLE DEPTH: 90 | SWEEP POSITION: | SWEEP START: | SWEEP END: | SWEEP LENGTH: | SWEEP TAPER: | PHASE COMP:

RECEIVER: TYPE: GSC 20d | PATTERN: IN LINE | NO. OF ELEMENTS: 18 | INLINE SPACING: | LATERAL SPACING:
CONNECTION: 50 SERIES PARALELL | RESISTANCE: 500 ohms | STAGGER: | LENGTH: | WIDTH: | LATERAL OFFSET:

SPREAD: NO. OF GROUPS: 48 | GROUP INTERVAL: 330' | SHOTPOINT INTERVAL: 1320' | FOLD: 6 | DIRECTION OF PROGRESSION:
OFFSET GROUP 1: | OFFSET GROUP ___: | OFFSET GROUP ___: | OFFSET GROUP 48/96: | LEADING GROUP:

DIAGRAMS/MISC. INFORMATION:



Note RN-2603 - RN 2617 Daily Instrument Tests
RN-2620 Test TB

SHOTPOINT	TR. 1 to 48 REEL NO.	REC.	TR ___ to ___ REEL NO.	REC.	SHOT SIZE	DEPTH	NO.	OFFSET	DIR.	SPREAD CDP SWITCH	LINE GROUPS	SET UP	REMARKS	CORR. STACK TR 1-48 HT.	REC.	TR 48-96 HT.	REC.
1	54316	2621			50	90	1			1/1	T-24 - SP7	1					
2		2622			50	90	2			1/5	T-20 - SP-8						
3		2623			50	90	3	495	EAST	1/9	T-16 - SP-9						
4		2624			50	90	4			1/13	T-12 - SP-10						
5		2625			50	90	5			1/17	T-8 - SP-11						
6		2626			50	90	6			1/21	T-4 - SP-12						
7		2627			50	90	7			1/25	SP-1 - SP-13						
8		2630			50	90	8			1/29	SP-2 - SP-14						
9		2631			50	90	9			1/33	SP-3 - SP-15						
10		2633			50	90	10			1/37	SP-4 - SP-16		RN-2632 misfire				
11		2634			50	90	11			1/41	SP-5 - SP-17						
12		2635			50	90	12			1/45	SP-6 - SP-18		TRACE #47 Dead				